



2/3" 2.8/50mm C		1/2"	1/3"
FOCAL LENGTH		f=50mm	
MAX. DIAMETER (RATIO)		F=1:2.8,4,8,16	
ELEMENT		4群 7枚	
PICTURE SIZE		6.6x8.8mm	4.8x6.4
ANGLE	VER. ANGLE	7.2°	5.2°
	HOR. ANGLE	9.6°	7.0°
	DIA. ANGLE	11.9°	8.7°
DISTORTION (TV)		-0.03%	-
SHOOTING RANGE AT	VER.	21.9mm	16.0
MINIMUM FOCUS	HOR.	29.3mm	21.3
DISTANCE	DIA.	36.6mm	26.6
MINIMUM FOCUS DISTANCE		0.2m	
FLANGE BACK		17.526 mm in air	
BACK FOCUS		35.5mm in air	
FILTER SCREW SIZE		M27.0x0.5	
FRONT/REAR EFFECTIVE DIA.		前 ϕ 21.7mm	後 ϕ 14.6mm
MOUNT		C-MOUNT	
EXIT PUPIL		-63.7	
TEMPERATURE RANGE		-10~+50°C	
STORING TEMPERATURE RANGE		-40~+60°C	
RESOLUTION CENTER/CORNER		中心100本/mm	周辺 80本/mm
WEIGHT		g	

NOTE: Specifications and availability are subject to change without notice
 注) 本仕様については、予告なしに変更する場合があります。

		尺度	1/1	承認	八木	製図	八木
		機種名	2/3" F2.8 f=50mm				
		1-25556					
2014.2.24	作成年月日						