EMI STA310 ومريم EMI STA310

Mobile industrial computer

New brand of industrial PC MobiPC[®] is mobile industrial PC with embedded screen with touch panel, also available version with built-in keyboard. These MobiPC[®] PCs are especially dedicated to mobile vision systems and mobile measurement systems.

- The smallest mobile industrial PC: 260 x 195 x 60 mm.
- Embedded screen LCD 8.9" with touch panel.
- Optional built-in keyboard.
- Modular construction with possibile expansion with additional components.
- Possible installation of many HDDs, including SDD.
- May be used as mobile video recoder for high speed industrial cameras with recording to memory or hard drives without loss of any image frames.
- Available optional accessory devices: monitors, synchronizers, temperature recorders, signal recorders.

Mobile products MobiPC[®] family



MobiPC[®] is a family of products that includes mobile industrial PCs, monitors and auxiliary devices especially used in mobile vision systems and mobile measuring systems.

The mobility of these devices has been ensured by the very small dimensions of the device housing, which in the case of MobiPC[®] Emi PC with built-in LCD screen and keyboard do not exceed 260 x 195 x 60 mm. And the weight of this PC does not exceed 2 kg. In addition, the housing is made of aluminum, so it is very durable and resistant to operation in different external conditions, and at the same time improves the cooling of electronics inside.

MobiPC® unification

MobiPC[®] is a unified housing system for various devices. The MobiPC[®] Emi model is based on the base format with dimensions 260 x 195 mm. Different enclosure models with different heights are available for different types of devices.

A standard set of mounting holes allows you to connect PC enclosures with other auxiliary devices in one pile, making the whole device more handy when moving. This increases the mobility of the whole equipment. Some of the mounting holes allows you to mount additional accessories such as a support, wall bracket, mounting plates for cameras and illuminators and many others.

Flexibility of MobiPC[®] configurations

The MobiPC[®] enclosures are prepared for the assembly of various PC components such as motherboards, HDD and SSD disks, LCD screens, touch panels, video interfaces, data acquisition boards, extension cards, keyboards, etc.. This is implemented using dedicated mounting frames and masking plates. Thanks to this, it is very easy to customize the configuration of equipment for specific user requirements.

The format of MobiPC[®] Emi enclosures allows to embed the LCD screen with a touch panel sized from 8.9 "to 10.1" and keyboard, which is an ideal solution for mobile video recording systems and mobile measurement systems.

Available MobiPC® devices

The set of available MobiPC[®] devices includes the following products:

- Mobile industrial PCs MobiPC[®] Emi series.
- Industrial monitors MobiPC® Emi series.
- Vision systems based on MobiPC[®] Emi PCs including video recorders and synchronizers.
- Measurement systems based on MobiPC[®] Emi PCs including temperature and signal recorders.



Technical Specifications

System		
CPU	Intel® Socket 1151 8-th gen Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron®	
Memory	DDR4 2 x SO-DIMM, max. 32GB	
Graphics card, scre	en	
Card type	Integrated, Intel HD	
LCD display	Optional, LCD 8.9", 1024 x 600 pixels	
Touch panel	Optional, resistive, single-touch	
HDMI output	Max. resolution 4096 x 2160 @ 24 Hz / 2560 x 1600 @ 60 Hz	
DisplayPort output	Max. resolution 4096 x 2304 @ 60 Hz	
Sound card		
Card type	Integrated, Realtek [®] ALC887-VD 8-channel High Definition Audio Codec	
Communication in	puts/outputs	
Ethernet	1 x RJ45 GigabitEthernet, Realtek [®] 8111H	
USB 3.0	2 external ports Gen1, 2 internal ports Gen1	
USB 2.0	2 external ports	
СОМ	1 internal RS-232 port	
Data storage		
System disk	1 x 128 GB, SSD, SATA 6 Gb/s	
Disks for data	Optionally, 1 x M.2 PCIe, 1 x SSD or HDD, SATA 6 Gb/s	
Power requiremen	ts	
Power requirements	DC 19 V or 12 V	
Power consumption	Min. 90 W	
Environmental requirements		
Operating temp.	0°C to +40°C	
Operating humidity	Relative humidity 10% to 90%	
Case, dimensions a	and weight	
Case	Aluminium, IP30	
Dimensions (LxWxH)	260 x 195 x 60 mm	
Weight	Up to 2.0 kg	
Standards, certifica	ates	
Standards	TBD	
Certificates	TBD	
Supported operati	ng systems	
Operating systems	Microsoft Windows® 10 Linux	


Ordering

orucing		
Available configurations		
EMI-STA310- CG4900T-STD	CPU Intel [®] Celeron [®] G4900T, RAM 4GB, SSD 128 GB SATA, without embedded display, without embedded keyboard, without operating system	
EMI-STA310- PG5500T-STD	CPU Intel [®] Pentium [®] G5500T, RAM 4GB, SSD 128 GB SATA, without embedded display, without embedded keyboard, without operating system	
EMI-STA310- I38100T-STD	CPU Intel [®] Core i3 [®] 8100T, RAM 8GB, SSD 128 GB SATA, without embedded display, without embedded keyboard, without operating system	
EMI-STA310- I58500T-STD	CPU Intel [®] Core i5 [®] 8500T, RAM 8GB, SSD 128 GB SATA, without embedded display, without embedded keyboard, without operating system	
EMI-STA310- I78700T-STD	CPU Intel [®] Core i7 [®] 8700T, RAM 16GB, SSD 128 GB SATA, without embedded display, without embedded keyboard, without operating system	


Options

Options		
EMI-SCR-LCD089T	Embedded LCD display 8.9", 1024 x 600 pixels, with single-touch resistive touch panel	
EMI-KBD-EMB	Embedded keyboard	
EMI-KBD-EXT	External wireless keyboard with touchpad	
EMI-PSP-DC19V120A	External power supply DC 19 V 120 W	
EMI-RAM-D4B04T08	Optional RAM 8 GB instead of 4 GB	
EMI-RAM-D4B04T16	Optional RAM 16 GB instead of 4 GB	
EMI-RAM-D4B04T32	Optional RAM 32 GB instead of 4 GB	
EMI-RAM-D4B08T16	Optional RAM 16 GB instead of 8 GB	
EMI-RAM-D4B08T32	Optional RAM 32 GB instead of 8 GB	
EMI-RAM-D4B16T32	Optional RAM 32 GB instead of 16 GB	
EMI-SSD-PCIE512G	SSD disk 512 GB, SATA 6 Gb/s	
EMI-SSD-PCIE001T	SSD disk 1 TB, SATA 6 Gb/s	
EMI-HDD-SATA001T	HDD disk 1 TB, SATA 6 Gb/s	
EMI-HDD-SATA002T	HDD disk 2 TB, SATA 6 Gb/s	
EMI-HDD-SATA003T	HDD disk 3 TB, SATA 6 Gb/s	
EMI-HDD-SATA004T	HDD disk 4 TB, SATA 6 Gb/s	
EMI-HDD-SATA005T	HDD disk 5 TB, SATA 6 Gb/s	
EMI-SFT-SYSWIN10P	Operating system Microsoft Windows [®] 10 Pro 64-bit	
EMI-SFT-SYSLNXU18	Operating system Linux Ubuntu 18 64-bit	
EMI-MNT-WMVESA	VESA wall mount	
EMI-MNT-STAND	Table stand with adjustable tilt angle	

Dimensions














200.0



Version without a keyboard

िम

° 0

0.

260.0

• ()